

# LEINOS 253

## Parquet Oil LF

**Application:** For heavily used wooden floors, stairs, Sterling OSB boards and similar interior surfaces.

**Technical Characteristics:** Parquet Oil LF 253 is a solvent-free mixture of oil and wax. It refines the wood permanently and guarantees a resistant surface. The wood structure is revitalised and receives a velvety sheen. Resistant to saliva and perspiration in accordance with DIN EN 53 160, after two applications. The film-forming oil-wax coating is very easy to care for.

**Color:** 002 Colourless, 202 White.

**Ingredients:** Linseed oil, ricin oil-natural resin boiling, wood oil-stand oil, wood oil-ricin oil-stand oil, micro wax, clay, kaolin, mineral pigments (except colourless), drying agents.

**Package Sizes:** 750ml / 2,5l / 10l

**Substrate and Preparation:** The substrate must be dry (wood moisture content max. 14 %) and free from greasy soiling. The application temperature should preferably not be below 16 °C. Drying behaviour is delayed at lower temperatures. Final sanding of the surfaces with at least 120 grit or grid.

**Processing:** Apply the Parquet Oil LF evenly once using a double-sided trowel (approx. 15-30 ml/m<sup>2</sup>, depending on the absorbency of the wood). Then pad thoroughly with a single disc polishing machine and green pad and polish the surface with a white pad. For heavily used or particularly absorbent floors, apply a second coat sparingly the next day. After 20-30 minutes, buff the surface with a white pad. Avoid layer formation at all costs! Please note: Floors must be laid without joints or levelled if necessary. If joints are present, oil may leak or noise may be generated when walking on the floor.

**Drying Time:** The drying time is approx. 6-12 hours (20-23 °C / 50-55 % relative humidity). Complete drying and full load-bearing capacity after 7-10 days. For reliable drying and to avoid odours, we always recommend the use of a fan to ensure sufficient air circulation on the surface during the drying phase.

**Consumption:** 15-30 ml/m<sup>2</sup>; coverage: 40-60 m<sup>2</sup>/litre.

**Storage and Shelf Life:** Store in a cool and dry place. Close container tightly. Stable for at least 2 years when originally sealed.

**Special Notes:** Work materials soaked in product with oil that is not completely dry should be stored in an airtight metal container/water and then disposed of, otherwise there is a risk of spontaneous combustion due to the vegetable oil content. The natural raw materials used may give off a typical odour. Wear approved respiratory protection when using spraying equipment. Wear a fine dust mask when sanding! VOC content: 1 g/l, EU limit value: 400 g/l (cat. e).  
GISCODE: BSL10 / EAK: 08 01 12

**Hazard statements:** Safety data sheet available on request.

**Precautionary statements:** Keep out of reach of children. IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Do NOT induce vomiting. Avoid release to the environment. Dispose of contents/container to an appropriate recycling or disposal facility.



# LEINOS 253

## Parquet Oil LF

To achieve optimal results, please observe the Technical Data Sheets of all products used. The information is based on the current state of our knowledge and experience. However, it does not constitute a guarantee of product properties and does not establish a contractual legal relationship. With the publication of this Technical Data Sheet, all previous information becomes invalid. Status: 24. März 2026